

2800 PSI**3100 PSI**

2800 PSI - G0071300 (50-State & Canada)
UPC: 696471072440

3100 PSI - G0071310 (50-State & Canada)
UPC: 696471072457

FEATURES

POWERFUL 208CC POWERMATE ENGINE

- Delivers maximum cleaning performance and reliability

HIGH PERFORMANCE AXIAL CAM PUMP

- Convenient, easy-to-reach pump connections

NOZZLES FOR A VARIETY OF APPLICATIONS

- 2800 - 0°, 25°, 40° and Soap
- 3100 - 0°, 15°, 25°, 40° and Soap

HIGH PRESSURE HOSE

- Non-marring
- Abrasion Resistant

ON BOARD DETERGENT TANK

- Conveniently use cleaning solutions to improve results
- Easy to access fill inlet

2800 psi • 3100 psi

specifications

PRESSURE AND FLOW

Max Outlet Pressure (psi/bar)	2800/193 3100/214
Max Flow Rate (gpm)/(L/min)	2.3/8.7 2.5/9.5

ENGINE

Manufacturer	Generac
Displacement (cc)	208
Type	4 cycle/OHV
Orientation	Horizontal
Lubrication Method	Splash
Low Oil Shutdown System	No
Fuel Capacity (qt/L)	3.5/3.3
Fuel On/Off Switch	Yes
Oil Capacity (oz/L)	20/0.6
Recommended Engine Oil	10W-30/SAE 30
Throttle Control	Fixed Speed
Choke	Manual
Starting Method	Recoil pull start

PUMP

Type	Axial Cam
Material	Aluminum
Maximum Water Supply Temperature (°F/°C)	100/38

HOSE

Type	PVC
Length (ft/m)	G0071300 - 25/7.6 G0071310 - 30/9.1
Diameter (in/mm)	0.3/8
Rating (psi/bar)	3100/214
Connectors	M22

DETERGENT SYSTEM

Chemical Tank	Yes
Chemical Tank Size (gal/L)	0.3/1.2

NOZZLES

Nozzle Descriptions	G0071300 - 0°, 25°, 40°, Soap G0071310 - 0°, 15°, 25°, 40°, Soap
---------------------	---

GUN & LANCE

Gun Type	Standard
Gun to Lance Connection	M22
Gun to Hose Connection	M22
Lance connection to Hose	Quick Change
Lance Length (in/cm)	21/53
Lance to Nozzle Connection	Quick Change

FRAME & MISC.

Handle	Fixed - Click In
Frame Construction	Welded Steel
Wheels - Never Flat (in/cm)	1.75 x 10/4.4 x 25.4

DIMENSIONS & WEIGHTS

Length (in/cm)	23.6/59.9
Width (wheel to wheel, in/cm)	19.7/49.9
Height (in/cm)	40.3/102.4
Unit Weight (lbs/kg)	57/25.9
Boxed Length (in/cm)	23.4/60
Boxed Width (in/cm)	20.4/52
Boxed Height (in/cm)	22/56
Boxed Weight (lb/kg)	65/33.4

WARRANTY

Warranty	2 year limited
----------	----------------