



- NOTES:
- 1) DRAWING CREATED FROM VENDOR 3D FILE. ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY. VENDOR TO NOTIFY GENERAC OF ANY DESIGN MODIFICATIONS.
  - 2) UL RECOGNIZED COMPONENT, REFERENCE UL FILE AU3493 VOLUME 15, SEC. 2. NO CHANGES TO CONSTRUCTION OR COMPONENTS WITHOUT GENERAC ENGINEERING APPROVAL.
  - 3) ALL FLEXIBLE LEADS TO BE UL RECOGNIZED (AVLWZ) MINIMUM RATINGS: 300V, 105°C, 20AWG.
  - 4) VENDOR: CHONGQING LHLUA AUTOMATIC TECHNOLOGY CO LTD PART NUMBER: TTS-4U.
  - 5) MAX EXCITATION VOLTAGE: 280VAC  
MAX EXCITATION CURRENT: 30A  
MAX OPERATING TEMP: -20°C TO 85°C
- MAX POWER RATING: 7.0 KW.
- (B)

OK7869  
AS VIEWED FROM  
FRONT OF HOUSING

**DRAWING CREATED FROM PRO/ENGINEER  
3D FILE. ECO MODIFICATION TO BE  
APPLIED TO SOLID MODEL ONLY.**

2/28/14	-A-	RELEASED FOR PRODUCTION
4/3/14	J8281B	DM 55 WAS 50. 40 WAS 33 247 WAS 22. 85 C WAS 105 C

GENERAL TOLERANCES UNLESS NOTED			
ALL XX : ± 0.4 MM	THIRD ANGLE PROJECTION		
XXXX : ± 0.5 MM			
ALL ANG : ± 1°			
DIFFERENT DIM AND TOL			
<p>GENERAL RULE : ALL DIMS ON THE COPIES (PRINT) OF THIS DRAWING MUST BE SPECIFIED TO THE NEAREST 0.1 MM UNLESS OTHERWISE NOTED.</p> <p>IT IS SPECIFIED WITHOUT THE DIMENSIONS AND TOLERANCE SYSTEMS :</p>			
DRAWN BY : IHB APPROVALS : DATE : 3/10/14			
ALL APPROVALS ELECTRICALLY STORED INSIDE WINDCHILL LUTECIFIC STATE : Production Released FIRST USE : 0005180			

TITLE			
AVR 7KW UL			
MATERIAL		GENERAC MATL SPECIFICATION	
SEE ABOVE		N/A	
SIZE	CAGE NO	DWG NO	REV
B	N/A	0K7869	B
SCALE	0.666	WT-KG	0.00
SHEET		1 of 1	