
# 1 of 2



# XC3000P

### 3" Trash Pump





#### **FEATURES**

- X-Frame Fully Wrapped, Heavy Duty 11
   Gauge Steel Frame provides rugged durability and protects the hose connections from damage
- Generac G-Force 265cc OHC engine with low-oil shutdown
- Large 2.9 gallon steel tank fuel tank with incorporated fuel gauge provides up to 4.3 hours of run time
- Steel Lifting Pocket designed for easier lifting and transportation on jobsites by crane or forklift

- Engraving Plate allows unit to be tagged / cataloged for use in contractor and rental fleets
- Color-coded suction and discharge ports to ensure the correct hose connections.
   (Blue = Discharge; Green= Suction)
- Easy Prime custom funnel design for quick and easy priming
- Durable silicon carbide mechanical seal for long life
- Onboard instructions with icons of key touch points make this pump easy to use

## **Specifications**

	4 1 (01)0
Engine Type	4 cycle/OHC
Engine Displacement (cc)	265
Start Type	Recoil Pull Start
Low Oil Shutdown Method	Low Level
Recommended Oil	10W-30 / SAE30
Fuel Capacity (gal/L)	2.9/10.9
Max Run Time	4.3 hrs
Max Flow gpm/lpm	350/1352
Max Total Head (ft/m)	90/27
Max Suction Lift (ft/m)	26/7.9
Mechanical Seal Type	Silicon Carbide
Solid Handling (in/mm)	1.2/30.48
Suction Port (in/mm) (NPT)	3/76.2
Discharge Port (in/mm) (NPT)	3/76.2
Pump Housing	Aluminum
Impeller	Ductile Cast Iron
Volute	Ductile Cast Iron

Strainer	Yes
Country of Origin	China
Warranty	3 Year
Assembled Length (L) (in/mm)	31.5/800
Assembled Width (W) (in/mm)	23.5/597
Assembled Height (H) (in/mm)	29.25/743
Unit Weight (lb/kg)	163/74
Carton Length (in/mm)	32.2/817
Carton Width (in/mm)	24.1/612
Carton Height (in/mm)	25.3/642
Shipping Weight (lb/kg)	173/78.5

