

Exploded view diagram of a 1997-2000 Ford 4.0L V6 engine. The diagram shows the engine block, cylinder head, and various accessories including the alternator, water pump, and timing belt. Components are labeled with numbers 1 through 42. Key features include:

- VIEW "A"**: Front view of the engine.
- VIEW "B"**: Side view of the engine.
- GROUND BAR**: Located at the bottom left.
- TO AIR CLEANER**: Arrow pointing to the air filter housing.
- SEE VIEW "A"**: Arrow pointing to the alternator area.
- SEE VIEW "B"**: Arrow pointing to the water pump area.

EXPLODED VIEW: EV ENGCOMPRT 9.0L G26 100KW CPL

DRAWING #: A0001403191

GROUP D

APPLICABLE TO:

ITEM	PART#	QTY.	DESCRIPTION
1	G049808	6	WASHER FLAT M12
2	G024310	1	PLUG STD PIPE 1/2 STEEL SQ HD
3	G057642	12	SCREW HHC M10-1.5 X 40 C8.8
4	0J8653	1	VALVE, PCV GN80L/GN90L
5	G047290	1	HOSE PCV (15"LG)
6	G049340	1	ADPTR BARB 90D 3/8 X 1/4NPT
7	0L0858	2	VALVE BALL 3/8 NPT M/F
8	G051769	6	WASHER LOCK M12
9	G055420	6	SCREW HHC M12-1.75 X 25 C10.9
10	0E4390	REF	GASKET GOVERNOR ACTUATOR
11	G026925	2	PLUG STD PIPE 3/8 STEEL SQ HD
12	0H7435	1	HARN LOW OIL PRESS SWITCH ASSY
13	G035579	1	BSHG RDCR HEX 1/4 TO 1/8
14	0K2179	1	FERRITE EMI CABLE CORE ASSY
15	G057823	2	CLAMP HOSE #10 .56-1.06
16	G050967	1	HOSE COOL 5/8 ID
17	0L4708	1	BARB, REDUCER 3/4 X 5/8
18	0H72370ST03	2	ENGINE FOOT, 9.0L G18
(2)19	G036833	6	SCREW HHC 3/8-16 X 1 G8
20	G022237	6	WASHER LOCK 3/8
21	G022131	18	WASHER FLAT 3/8-M10 ZINC
22	0A8240	3	FLEX PLATE SAE10
(2)23	0J4574	8	SCREW SHC M10-1.5 X 25 C8.8
24	G046526	20	WASHER LOCK M10
25	G070264	8	WASHER FLAT M10
26	G022333	1	SCREW HHC 7/16-14 X 1 G5
27	G022302	1	WASHER LOCK 7/16
28	G022250	3	WASHER FLAT 7/16 ZP
29	0D2244M	1	ASSY MAGPICKUP(3/8-24 MALE)
30	G043116	1	SCREW HHC M6-1.0 X 12 G8.8
31	G022097	1	WASHER LOCK M6-1/4
32	G022473	1	WASHER FLAT 1/4-M6 ZINC
33	10000010781	1	WATER PUMP INLET EXTENSION ASSEMBLY 9.0L
34	G035685	2	CLAMP HOSE #28 1.32-2.25
35	10000010965	1	HOSE-WATER PUMP INLET
36	G025507	1	WASHER LOCK EXT 7/16 STL
37	057795B	1	BARBED EL 90 5/8 PLASTIC
38	0G5954	REF	GROMMET .625 X 1.25 X .433
39	A0001443376	1	HARN COMPLETE G9.0L G26 N/A W/EVO CTRL (NOT SHOWN)
40	069860E	1	ASSY HOSE OIL DRAIN 28 INCH
41	G043790	1	BARBED EL 90 3/8 NPT X 3/8
42	G062303	2	ADAPTOR 1/4 NPT TO 3/8 NPT

NOTES (UNLESS OTHERWISE SPECIFIED):

(1) ALL STANDARD HARDWARE TO BE TORQUE PER EDS001.

(2) TORQUE VALUES:

I/N 2 – 31FT-LBS

I/N 23 – 28FT-LBS (WITH LOCTITE 242)

I/N 19 – 34FT-LBS (WITH LOCTITE 242)