



I/N	DESCRIPTION	FUNCTION
1	3/8" NPT COUPLING	FUEL SUPPLY
2	2" NPT O.P.V.	FUEL FILL / OVERFILL PREVENTION VALVE
3	FUEL LEVEL GAUGE	ELECTRONIC SENDOR / VISUAL GAUGE
4	3/8" NPT COUPLING	FUEL RETURN
5	2" NPT WELD FLANGE	NORMAL VENT
6	3" NPT WELD FLANGE	INNER TANK EMERGENCY VENT
7	1/2" NPT HALF COUPLING	OUTER TANK LEAK DETECTOR
8	3" NPT WELD FLANGE	OUTER TANK EMERGENCY VENT
9	1/2" NPT HALF COUPLING	FLUID BASIN ALARM
10	2" NPT WELD FLANGE	CUSTOMER USE

TANK P/N	0J82750ST03
TOTAL CAPACITY	818 [216]
USABLE CAPACITY	795 [210]
DRY WEIGHT	465 [1026]

CAPACITY: LITER [GALLONS]
WEIGHT: KILOGRAMS [POUNDS]
DIMENSIONS: MM [INCH]

UL #142 LISTED

DRAWING CREATED FROM PRO/ENGINEER 3D FILE. ECO MODIFICATION TO BE APPLIED TO SOLID MODEL ONLY.

INSTALLATION DRAWING

GENERAC POWER SYSTEMS OWNS THE COPYRIGHT OF THIS DRAWING WHICH IS SUPPLIED IN CONFIDENCE AND MUST NOT BE USED FOR ANY PURPOSE OTHER THAN FOR WHICH IT IS SUPPLIED WITHOUT THE EXPRESS WRITTEN CONSENT OF GENERAC POWER SYSTEMS. © GENERAC POWER SYSTEMS 2012

ELECTRONICALLY APPROVED
INSIDE WINDCHILL

LIFECYCLE STATE: Production Released

TITLE

INSTALL BASETANK B-GRP
210 GAL W/ FLUID CONTAINMENT

ISSUE DATE: 06/07/12

SIZE B	CAGE NO N/A	DWG NO 0J8972	REV A
-----------	----------------	------------------	----------

SCALE 0.060	WT-KG	SHEET 1 of 1
----------------	-------	-----------------