



TORQUE SPECIFICATIONS

▲ TORQUE TO 20 LB-IN. MIN.

△ TORQUE TO 24-30 LB-IN. MIN.

△ TORQUE TO 45-50 LB-IN. MIN.

**EXPLODED VIEW:AV GEN READY LOAD CENTER PANELBD
DRAWING #: 0G6421AV**

GROUP C

APPLICABLE TO:

ITEM	PART #	QTY.	DESCRIPTION
1	0G6421	1	GEN READY LOAD CENTER 42 CIRCUIT,200A .
2	0G6421A	1	DOOR T RIM , 42"
3	0G6421B	3	DOOR T RIM , M OLDE D HINGE
4	0J1505	1	DOOR T RIM , LATCH BLANK
5	0G6421D	1	DOOR T RIM , DOOR 42" LC BOX
6	0G6421E	1	DOOR T RIM , DE CAL
7	0G6421F	1	BAG S/A WITH 6 TRIM S CREWS
8	0G6421G	1	UPPER PAN, HIGH AMP 42" ENCL.
9	0G6421H	2	SCREW, 10-32 FLUSH ADJ.(DEADFRONT)
10	0G6421J	1	BOX ASSY, INDOOR L/C 42"
11	0G6421K	1	GROUND BAR W 2/0 LUG, 32 S CREWS
12	0G6421L	1	SCREW- #10-32 X .88 SHWHS TT
13	0G6421M	1	SCREW- #10-32 X 1.00 SHWHS TT
14	0G6421N	1	NEUTRAL TIE STRIP
15	0G6421P	1	BOND-S TRAP
16	0G6421Q	1	SCREW- #10-32 X .375 SHWHS TT
17	0G6421R	1	INSULATED NEUTRAL 41 SCREWS
18	0G6421S	2	SCREW- #10-32 X 7/16 SP PH TAPTITE
19	0G6421T	1	SCREW- #10-32 X .75 CRP HTT
20	0G6421U	1	BASEPAN UPPER MODULE
21	0G6421V	1	BASEPAN MID MODULE (6 POS)
22	0G6421W	3	BASEPAN LOWER MODULE 8 CIR. (4 POS)
23	0G6421X	1	BRIDGE MURRAY LOADCENTER (METAL)
24	0G6421Y	1	SCREW HHTT #10-32 X .562 HHWT
25	0G6421Z	3	BUSBAR 100-150A CU LH
26	0G6421AA	1	BUSBAR 100-150A CU RH
27	0G6421AB	1	BUSBAR 200A CU LH
28	0G6421AC	1	BUSBAR 200A CU RH
29	0G6421AD	1	STUD,PRESS 1/4-20 X 5/8
30	0G6421AE	4	HEX CONICAL SEMS NUT (1/4-20)
31	0G6421AF	4	CIRCUIT BREAKER 200A 4P 120/240V 22K MAIN
32	0F7888H	1	CIRCUIT BREAKER 125A 2-POLE (SIEMENS)
33	0G6421AH	1	WIREFORM, 1/0 CU UPPER BRIDGE WIRE (SM)
34	0G6421AJ	1	WIREFORM, 1/0 CU LOWER BRIDGE WIRE (LG)
35	0G6421AK	1	SWITCH, 125A 2-POLE MOLDED CASE
36	0G6421AL	1	RETAINER CLIP MAIN BREAKER
37	0G6421AM	1	SCREW, #6 X .19 ROUND HEAD
38	0G6421AN	1	CARTON 42" (NOT SHOWN)
39	0G6421AP	1	GENERATOR INFORMATION, DE CAL
40	0G6421AQ	1	VOLTAGE SENSING CB, DE CAL
41	0G6421AR	1	GEN READY ACCESSORY, DE CAL
42	0G6421A	1	DECAL, GEN-READY LC SERIAL NUMBER