

200A 250VAC

TMS200

200A Manual Transfer Switch

1 of 2

The Generac TMS200 Manual Transfer Switch

Designed for ease of installation with the flexibility for multiple application options

Flexibility and control for temporary generators

Integrated camlock functionality for mobile generator sources



Image used for illustration purposes only.

Features

- ALUMINUM CONSTRUCTION
- POWDER-COATED UL TYPE / NEMA 3R ENCLOSURE
- STAINLESS STEEL HARDWARE
- INTEGRATED CAMLOCK “QUICK CONNECT” CAPABILITY
- UTILITY POWER FAIL RELAY ALARM
- SLIDEBAR-TYPE MECHANICAL INTERLOCK
- HINGED “PADLOCKING” DOORS
- FIELD MODIFIED DOOR SWING
- UL1008 LISTED

Optional Features

- EXTENDED WARRANTY AVAILABLE
- THREE-PHASE VOLTAGE CONFIGURATIONS AVAILABLE

Codes and Standards

Generac products are designed to the following standards:



UL1008,
UL508,
UL50,
CSA C22.2 No. 178



NEC 702




NEMA 250

Application and Engineering Data

2 of 2

Cabinet Specifications	
Dimensions	20"W x 10"D x 36"H
Weight	53.8 lbs.
Construction	Single Chamber with Main Door
	0.080 14GA Aluminum
	UL Type / NEMA 3R Rated
	Powder Coat Finish for Corrosion Resistance
	UL Listed - Non-Automatic Transfer Switch & Suitable for Service Equipment
	Stainless Steel Hardware
Mounting Options	3-Point Latching System with Pad-Lockable Handle
	Wall
Installed	H-frame
	Pre-wired alarm terminal strip

Electrical Specifications	
Voltage/Phase/Amps	120/240 Single-Phase, 200A 120/208 3-Phase, 200A 120/240 3-Phase, 200A
Breaker	Generac 200 amp Utility Breaker Generac 200 amp Generator Breaker
Fault Current Rating	22k AIC Rated
200A Camlock Generator Connection	Single-Phase: Black L1, Red L2, White-Neutral, Green-Ground
	3-Phase: Black L1, Red L2, Blue L3, White-Neutral, Green-Ground
	Uses 4 CH E1016 Male Connectors
	Mating Connector – CH E1016 Female
Input to Generator	350MCM - #6 AWG
Output to Site	350MCM - #6 AWG
Generator Annunciator Connector	Deutsch DTM04-12PA-L012
Alarm Terminal Board	Generator Run Alarm
	Generator Fail – Shutdown Alarm
	Generator Fail – Non Shutdown Alarm
	Low Fuel Alarm
	Generator Theft Alarm
	AC Utility Fail Alarm

Additional Components		
Mounting Bracket	Installation Mounting Bracket	 <p>Shipped loose with switch</p>
Alarm Cable	100' length of multi-conductor cable	
Enclosure Gasket	Full Exterior x 2"W x 1/2"D Closed Cell Gasket	

Specification characteristics may change without notice. Dimensions and weights are for preliminary purposes only. Please consult a Generac Power Systems Industrial Dealer for detailed installation drawings.

Generac Power Systems, Inc. • S45 W29290 HWY. 59, Waukesha, WI 53189 • generac.com

©2013 Generac Power Systems, Inc. All rights reserved. All specifications are subject to change without notice. Bulletin 0195630SBY-E / Printed in U.S.A. 03/13/13